



Model: AE4425Y-AA1A (AE4425Y-AA)

Product Description

Type: Reciprocating
Application: HBP/CBP - High/Commercial
 Back Pressure
Refrigerant: R-134a
Voltage/Frequency: 115V ~ 60Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE (R-134a)	115V ~ 60HZ	2750	693	806	340	8.09	2.04	2.37	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE (R-513A)	115V ~ 60HZ	2850	718	835	368	7.75	1.95	2.27	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 9
Weight Unit of Measure: KG
Displacement (cc): 6.69
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 284.9

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 20
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 3.6
Max. Continuous Current (MCC in Amps): 5.5
Motor Resistance (Ohm) - Main: 2.585
Motor Resistance (Ohm) - Start: 4.56
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, SASO Listed, cURus Recognized