



## Model: AE4430Z-GS1A (AE4430Z-GS)

### Product Description

**Type:** Reciprocating  
**Application:** HBP/CBP - High/Commercial  
 Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 220V ~ 60Hz 220V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V ~ 60HZ	3400	857	997	431	7.89	1.99	2.31	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE	220V ~ 50HZ	2850	718	835	354	8.05	2.03	2.36	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 10  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 5.16  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 284.9

#### Electrical

**Voltage Range (50 Hz):** 180-242  
**Voltage Range (60 Hz):** 187-242  
**Locked Rotor Amps (LRA):** 14.5  
**Rated Load Amps (RLA 50 Hz):** 2.26  
**Rated Load Amps (RLA 60 Hz):** 2.37  
**Max. Continuous Current (MCC in Amps):** 3.47  
**Motor Resistance (Ohm) - Main:** 7.802  
**Motor Resistance (Ohm) - Start:** 10.228  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, SGS Listed, VDE Listed, cURus Recognized