



## Model: AE4440Y-GS1B (AE4440Y-GS)

### Product Description

**Type:** Reciprocating  
**Application:** HBP/CBP - High/Commercial  
 Back Pressure  
**Refrigerant:** R-134a  
**Voltage/Frequency:** 220V ~ 60Hz 220V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	220V ~ 60HZ	3761	947	1101	493	7.62	1.92	2.23	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)
EN12900	220V ~ 50HZ	3134	789	918	407	7.7	1.94	2.25	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 11  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 10.33  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 280

#### Electrical

**Voltage Range (50 Hz):** 180-242  
**Voltage Range (60 Hz):** 187-242  
**Locked Rotor Amps (LRA):** 18.4  
**Rated Load Amps (RLA 50 Hz):** 3  
**Rated Load Amps (RLA 60 Hz):** 3  
**Max. Continuous Current (MCC in Amps):** 4.9  
**Motor Resistance (Ohm) - Main:** 1.692  
**Motor Resistance (Ohm) - Start:** 3.756  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE  
 Listed, SASO Listed, UL Recognized