



Model: AE4460Z-AA1C (AE4460Z-AA)

Product Description

Type: Reciprocating
Application: HBP/CBP - High/Commercial
 Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 115V ~ 60Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	6850	1726	2008	912	7.51	1.89	2.2	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 11
Weight Unit of Measure: KG
Displacement (cc): 10.33
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 386.65

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 50.5
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 10.15
Max. Continuous Current (MCC in Amps): 12.2
Motor Resistance (Ohm) - Main: .662
Motor Resistance (Ohm) - Start: 3.358
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, cURus Recognized