



## Model: AG2511X-TZ1A (TAG2513X)

---

### Product Description

Type:	Reciprocating
Application:	LBP - Low Back Pressure
Refrigerant:	MULTI
Voltage/Frequency:	440V 3~ 60Hz 400V 3~ 50Hz
Version:	N/A

---

### Product Specifications

#### General

Evaporating Temp. Range:	-40°C to -12.2°C (-40°F to 10°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

#### Mechanical

Weight:	0
Weight Unit of Measure:	N/A
Displacement (cc):	100.7
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	1960

#### Electrical

Voltage Range (50 Hz):	340-440
Voltage Range (60 Hz):	396-499
Locked Rotor Amps (LRA):	42.5
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	0
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	4.6
Motor Resistance (Ohm) - Start:	4.6
Motor Type:	3PH
Overload Type:	N/A
Relay Type:	N/A

#### Agency Approval

N/A