



Model: AGB2511ZKZ (TAG2513Z)

Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 220V 3~ 60Hz 220V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V 3~ 50HZ	5434	1369	1592	1611	3.37	.85	.98	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)
EN12900	220V 3~ 60HZ	7243	1825	2122	2021	3.58	.9	1.05	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 46
Weight Unit of Measure: KG
Displacement (cc): 100.7
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 1960

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 86
Rated Load Amps (RLA 50 Hz): 7.8
Rated Load Amps (RLA 60 Hz): 8.3
Max. Continuous Current (MCC in Amps): 19.6
Motor Resistance (Ohm) - Main: .95
Motor Resistance (Ohm) - Start: .95
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed