



## Model: AGB2520ZTZ (TAG2525Z)

### Product Description

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 440V 3~ 60Hz 400V 3~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	400V 3~ 50HZ	10270	2588	3009	2659	3.86	.97	1.13	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)
EN12900	440V 3~ 60HZ	12965	3267	3798	3349	3.87	.97	1.13	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)

#### General

**Evaporating Temp. Range:** -40°C to -12.2°C (-40°F to 10°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 0  
**Weight Unit of Measure:** N/A  
**Displacement (cc):** 145  
**Oil Type:** N/A  
**Viscosity (cSt):** N/A  
**Oil Charge (cc):** 1960

#### Electrical

**Voltage Range (50 Hz):** 340-440  
**Voltage Range (60 Hz):** 396-499  
**Locked Rotor Amps (LRA):** 58  
**Rated Load Amps (RLA 50 Hz):** 6.3  
**Rated Load Amps (RLA 60 Hz):** 6.9  
**Max. Continuous Current (MCC in Amps):** 13.3  
**Motor Resistance (Ohm) - Main:** 2.9  
**Motor Resistance (Ohm) - Start:** 2.9  
**Motor Type:** 3PH  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

**CCC Listed, CE Listed, GOST RUSSIA Listed, GOST  
UKRAINE Listed, VDE Listed**