



## Model: AGB4546TKZ (TAGP4546T)

### Product Description

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-22  
**Voltage/Frequency:** 220V 3~ 60Hz 220V 3~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	220V 3~ 50HZ	17662	4451	5175	2390	7.39	1.86	2.17	-10°C (14°F)	45°C (113°F)	32°C (90°F)	0°C (32°F)	45°C (113°F)

#### General

**Evaporating Temp. Range:** -6.7°C to 12.8°C (20°F to 55°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 44  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 90.2  
**Oil Type:** Mineral  
**Viscosity (cSt):** 68  
**Oil Charge (cc):** 1960

#### Electrical

**Voltage Range (50 Hz):** 180-253  
**Voltage Range (60 Hz):** 187-264  
**Locked Rotor Amps (LRA):** 99  
**Rated Load Amps (RLA 50 Hz):** 13.5  
**Rated Load Amps (RLA 60 Hz):** 12.9  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** .9  
**Motor Resistance (Ohm) - Start:** .9  
**Motor Type:** 3PH  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE  
 Listed