



Model: AGB4553TTZ (TAGP4553T)

Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-22
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	24908	6277	7298	3635	6.85	1.73	2.01	-10°C (14°F)	45°C (113°F)	32°C (90°F)	0°C (32°F)	45°C (113°F)
EN12900	400V 3~ 50HZ	20969	5284	6144	2856	7.34	1.85	2.15	-10°C (14°F)	45°C (113°F)	32°C (90°F)	0°C (32°F)	45°C (113°F)

General

Evaporating Temp. Range: -6.7°C to 12.8°C (20°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 46
Weight Unit of Measure: KG
Displacement (cc): 100.7
Oil Type: Mineral
Viscosity (cSt): 68
Oil Charge (cc): 1960

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 44.3
Rated Load Amps (RLA 50 Hz): 6.7
Rated Load Amps (RLA 60 Hz): 7.6
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: N/A
Motor Resistance (Ohm) - Start: N/A
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

**CE Listed, GOST RUSSIA Listed, GOST UKRAINE
Listed**