



## Model: AH2466X-TZ1C (TFH2480X)

---

### Product Description

|                    |                           |
|--------------------|---------------------------|
| Type:              | Reciprocating             |
| Application:       | LBP - Low Back Pressure   |
| Refrigerant:       | MULTI                     |
| Voltage/Frequency: | 440V 3~ 60Hz 400V 3~ 50Hz |
| Version:           | N/A                       |

---

### Product Specifications

#### General

|                          |                                  |
|--------------------------|----------------------------------|
| Evaporating Temp. Range: | -40°C to -12.2°C (-40°F to 10°F) |
| Motor Torque:            | High Start Torque (HST)          |
| Compressor Cooling:      | N/A                              |

#### Mechanical

|                         |             |
|-------------------------|-------------|
| Weight:                 | 0           |
| Weight Unit of Measure: | N/A         |
| Displacement (cc):      | 53.2        |
| Oil Type:               | Polyolester |
| Viscosity (cSt):        | 32          |
| Oil Charge (cc):        | 1625        |

#### Electrical

|  |     |
|--|-----|
| Voltage Range (50 Hz):                 | N/A |
| Voltage Range (60 Hz):                 | N/A |
| Locked Rotor Amps (LRA):               | 0   |
| Rated Load Amps (RLA 50 Hz):           | 2.6 |
| Rated Load Amps (RLA 60 Hz):           | 2.7 |
| Max. Continuous Current (MCC in Amps): | 0   |
| Motor Resistance (Ohm) - Main:         | 6   |
| Motor Resistance (Ohm) - Start:        | N/A |
| Motor Type:                            | N/A |
| Overload Type:                         | N/A |
| Relay Type:                            | N/A |

#### Agency Approval

N/A