



## Model: AH2490X-TZ1C (TFH2511X)

---

### Product Description

Type:	Reciprocating
Application:	LBP - Low Back Pressure
Refrigerant:	MULTI
Voltage/Frequency:	440V 3~ 60Hz 400V 3~ 50Hz
Version:	N/A

---

### Product Specifications

#### General

Evaporating Temp. Range:	-40°C to -12.2°C (-40°F to 10°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	N/A

#### Mechanical

Weight:	0
Weight Unit of Measure:	N/A
Displacement (cc):	74.25
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	1625

#### Electrical

Voltage Range (50 Hz):	N/A
Voltage Range (60 Hz):	N/A
Locked Rotor Amps (LRA):	0
Rated Load Amps (RLA 50 Hz):	3.3
Rated Load Amps (RLA 60 Hz):	3.4
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	5.11
Motor Resistance (Ohm) - Start:	N/A
Motor Type:	N/A
Overload Type:	N/A
Relay Type:	N/A

#### Agency Approval

N/A