



Model: AHA2466AXD (AHA2466A)

Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-12
Voltage/Frequency: 208-230V ~ 60Hz 200V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	230V ~ 60HZ	6600	1663	1934	1750	3.77	.95	1.11	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 78
Weight Unit of Measure: LB
Displacement (cc): 74.165
Oil Type: N/A
Viscosity (cSt): N/A
Oil Charge (cc): 1124

Electrical

Voltage Range (50 Hz): 180-220
Voltage Range (60 Hz): 187-254
Locked Rotor Amps (LRA): 71
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 9.7
Max. Continuous Current (MCC in Amps): 15.1
Motor Resistance (Ohm) - Main: .68
Motor Resistance (Ohm) - Start: 3.58
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, UL Recognized, cURus Recognized