



## Model: AHC2466ZTZ (TFH2480Z)

### Product Description

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 440V 3~ 60Hz 400V 3~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	3430	864	1005	1314	2.61	.66	.76	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)
EN12900	400V 3~ 50HZ	2983	752	874	1102	2.71	.68	.79	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

#### General

**Evaporating Temp. Range:** -40°C to -12.2°C (-40°F to 10°F)  
**Motor Torque:** N/A  
**Compressor Cooling:** N/A

#### Mechanical

**Weight:** 33  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 53.2  
**Oil Type:** N/A  
**Viscosity (cSt):** N/A  
**Oil Charge (cc):** 0

#### Electrical

**Voltage Range (50 Hz):** N/A  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 0  
**Rated Load Amps (RLA 50 Hz):** 2.6  
**Rated Load Amps (RLA 60 Hz):** 2.7  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** 6  
**Motor Resistance (Ohm) - Start:** N/A  
**Motor Type:** N/A  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

**CCC Listed, CE Listed, GOST RUSSIA Listed, GOST  
UKRAINE Listed, IRAM Listed, SASO Listed, VDE  
Listed**