



Model: AHC2490ZHZ (FH2511Z)

Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 208-220V ~ 60Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V ~ 60HZ	4802	1210	1407	1915	2.51	.63	.73	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque: N/A
Compressor Cooling: N/A

Mechanical

Weight: 38
Weight Unit of Measure: KG
Displacement (cc): 74.25
Oil Type: N/A
Viscosity (cSt): N/A
Oil Charge (cc): 0

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 0
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 12
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: .5
Motor Resistance (Ohm) - Start: 2.55
Motor Type: N/A
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, SASO Listed, UL Recognized, cURus Recognized