



## Model: AHC4522ZTZ (TFHP4522Z)

### Product Description

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 440V 3~ 60Hz 400V 3~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	20399	5141	5977	2394	8.52	2.15	2.5	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)
EN12900	400V 3~ 50HZ	17324	4366	5076	1995	8.68	2.19	2.54	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** N/A  
**Compressor Cooling:** N/A

#### Mechanical

**Weight:** 31  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 39.95  
**Oil Type:** N/A  
**Viscosity (cSt):** N/A  
**Oil Charge (cc):** 0

#### Electrical

**Voltage Range (50 Hz):** N/A  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 0  
**Rated Load Amps (RLA 50 Hz):** 3.8  
**Rated Load Amps (RLA 60 Hz):** 4  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** 6.28  
**Motor Resistance (Ohm) - Start:** N/A  
**Motor Type:** N/A  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

**CE Listed, GOST RUSSIA Listed, GOST UKRAINE  
Listed, VDE Listed**