



Model: AHC4540ZHZ (FH4540Z)

Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 208-220V ~ 60Hz
Version: N/A

Product Specifications

Performance

| Condition | Test Voltage | Refrigeration Capacity | | | Input Power | Efficiency | | | EVAP TEMP | COND TEMP | AMBIENT TEMP | RETURN GAS | LIQUID TEMP |
|-----------|--------------|------------------------|--------|-------|-------------|------------|---------|------|------------|--------------|--------------|-------------|--------------|
| | | Btu/h | kcal/h | W | W | Btu/Wh | kcal/Wh | W/W | | | | | |
| EN12900 | 220V ~ 60HZ | 36761 | 9264 | 10771 | 4856 | 7.57 | 1.91 | 2.22 | 5°C (41°F) | 45°C (113°F) | 32°C (90°F) | 15°C (59°F) | 45°C (113°F) |

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: N/A
Compressor Cooling: N/A

Mechanical

Weight: 36
Weight Unit of Measure: KG
Displacement (cc): 74.25
Oil Type: N/A
Viscosity (cSt): N/A
Oil Charge (cc): 0

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 0
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 25
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: .42
Motor Resistance (Ohm) - Start: 2.33
Motor Type: N/A
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, UL Recognized, cURus Recognized