



## Model: AJ2433Z-KZ1C (TAJ2446Z)

### Product Description

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 220V 3~ 60Hz 220V 3~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V 3~ 50HZ	2163	545	633	593	3.64	.91	1.06	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)
EN12900	220V 3~ 60HZ	2780	700	814	702	3.96	.99	1.16	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)

#### General

**Evaporating Temp. Range:** -40°C to -12.2°C (-40°F to 10°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 21  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 26.15  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 475

#### Electrical

**Voltage Range (50 Hz):** 180-253  
**Voltage Range (60 Hz):** 187-264  
**Locked Rotor Amps (LRA):** 29  
**Rated Load Amps (RLA 50 Hz):** 3.1  
**Rated Load Amps (RLA 60 Hz):** 3.1  
**Max. Continuous Current (MCC in Amps):** 7.3  
**Motor Resistance (Ohm) - Main:** 3.42  
**Motor Resistance (Ohm) - Start:** 3.42  
**Motor Type:** 3PH  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

**CE Listed, GOST RUSSIA Listed, GOST UKRAINE  
Listed**