



Model: AJ2444Z-KZ1C (TAJ2464Z)

Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 220V 3~ 60Hz 220V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	220V 3~ 50HZ	2849	717	834	791	3.6	.9	1.05	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)
EN12900	220V 3~ 60HZ	3247	818	951	899	3.61	.91	1.05	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	20°C (68°F)	40°C (104°F)

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 21
Weight Unit of Measure: KG
Displacement (cc): 34.45
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 180-253
Voltage Range (60 Hz): 187-264
Locked Rotor Amps (LRA): 35
Rated Load Amps (RLA 50 Hz): 3.7
Rated Load Amps (RLA 60 Hz): 3.9
Max. Continuous Current (MCC in Amps): 8.3
Motor Resistance (Ohm) - Main: 2.96
Motor Resistance (Ohm) - Start: 2.96
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

**CE Listed, GOST RUSSIA Listed, GOST UKRAINE
Listed**