



## Model: AJ4461A-XA1C (CAJ4461A)

### Product Description

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-12  
**Voltage/Frequency:** 115V ~ 60Hz 100V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	100V ~ 50HZ	4629	1166	1356	687	6.73	1.69	1.97	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)
EN12900	115V ~ 60HZ	5446	1372	1595	834	6.52	1.64	1.91	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 18  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 18.3  
**Oil Type:** Mineral  
**Viscosity (cSt):** 68  
**Oil Charge (cc):** 475

#### Electrical

**Voltage Range (50 Hz):** 90-110  
**Voltage Range (60 Hz):** 103-127  
**Locked Rotor Amps (LRA):** 46  
**Rated Load Amps (RLA 50 Hz):** 10  
**Rated Load Amps (RLA 60 Hz):** 10  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** .7  
**Motor Resistance (Ohm) - Start:** 5  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed