



Model: AJ4492A-HZ1C (CAJ4492A)

Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-12
Voltage/Frequency: 208-220V ~ 60Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V ~ 60HZ	8290	2089	2428	1189	6.97	1.75	2.04	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 19
Weight Unit of Measure: KG
Displacement (cc): 25.95
Oil Type: Mineral
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): 187-242
Locked Rotor Amps (LRA): 35.5
Rated Load Amps (RLA 50 Hz): 6.6
Rated Load Amps (RLA 60 Hz): 6.6
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 1.5
Motor Resistance (Ohm) - Start: 10
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed