



Model: AJ5510E-XA3C (AJ5510E)

Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 115V ~ 60Hz 100V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	100V ~ 50HZ	7612	1918	2230	986	7.72	1.94	2.26	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	115V ~ 60HZ	8960	2257	2625	1136	7.88	1.98	2.31	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 18
Weight Unit of Measure: KG
Displacement (cc): 18.6
Oil Type: Mineral
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 90-110
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 63
Rated Load Amps (RLA 50 Hz): 11.2
Rated Load Amps (RLA 60 Hz): 11.7
Max. Continuous Current (MCC in Amps): 17.3
Motor Resistance (Ohm) - Main: .52
Motor Resistance (Ohm) - Start: 6.21
Motor Type: PSC
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed