



Model: AJ5512C-CZ3C (AJ5512C)

Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-407C
Voltage/Frequency: 230V ~ 60Hz 208V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	208V ~ 50HZ	8163	2057	2391	1096	7.44	1.87	2.18	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	230V 3~ 60HZ	9530	2401	2792	1284	7.42	1.87	2.17	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 18
Weight Unit of Measure: KG
Displacement (cc): 21.75
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 187-230
Voltage Range (60 Hz): 207-253
Locked Rotor Amps (LRA): 33
Rated Load Amps (RLA 50 Hz): 7.2
Rated Load Amps (RLA 60 Hz): 6.7
Max. Continuous Current (MCC in Amps): 9.7
Motor Resistance (Ohm) - Main: 2.1
Motor Resistance (Ohm) - Start: 10.4
Motor Type: PSC
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed