



Model: AJ5512E-GZ3C (AJ5512E)

Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 208-220V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V ~ 50HZ	9135	2302	2676	1177	7.76	1.95	2.27	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 18
Weight Unit of Measure: KG
Displacement (cc): 21.75
Oil Type: Mineral
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 187-242
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 32
Rated Load Amps (RLA 50 Hz): 7.2
Rated Load Amps (RLA 60 Hz): 7.2
Max. Continuous Current (MCC in Amps): 9.7
Motor Resistance (Ohm) - Main: 2.1
Motor Resistance (Ohm) - Start: 10.5
Motor Type: PSC
Overload Type: N/A
Relay Type: N/A

Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed