



Model: AJ5515E-TZ1C (TAJ5515E)

Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	400V 3~ 50HZ	11476	2891	3362	1343	8.54	2.15	2.5	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	440V 3~ 60HZ	13519	3406	3961	1725	7.83	1.97	2.29	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 19
Weight Unit of Measure: KG
Displacement (cc): 25.95
Oil Type: Mineral
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 23
Rated Load Amps (RLA 50 Hz): 3.9
Rated Load Amps (RLA 60 Hz): 3.9
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 11.4
Motor Resistance (Ohm) - Start: 11.4
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

**CCC Listed, CE Listed, GOST RUSSIA Listed, GOST
UKRAINE Listed**