



Model: AJ5519E-CZ3C (AJ5519E)

Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 230V ~ 60Hz 208V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 60HZ	17762	4476	5204	2294	7.74	1.95	2.26	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	208V ~ 50HZ	15088	3802	4420	1888	7.99	2.01	2.34	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 21
Weight Unit of Measure: KG
Displacement (cc): 34.45
Oil Type: Mineral
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 187-230
Voltage Range (60 Hz): 207-253
Locked Rotor Amps (LRA): 57
Rated Load Amps (RLA 50 Hz): 10.7
Rated Load Amps (RLA 60 Hz): 10.7
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: .9
Motor Resistance (Ohm) - Start: 5.6
Motor Type: PSC
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed