



Model: AJK480T-TZ1C (TAJ9480T)

Product Description

Type: Reciprocating
Application: MBP/HBP - Medium/High Back Pressure
Refrigerant: R-22
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	400V 3~ 50HZ	6719	1693	1968	824	8.15	2.05	2.38	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)
EN12900	440V 3~ 60HZ	7916	1994	2319	1050	7.53	1.89	2.2	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 19
Weight Unit of Measure: KG
Displacement (cc): 15.2
Oil Type: Synthetic Alkylate
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 13
Rated Load Amps (RLA 50 Hz): 1.8
Rated Load Amps (RLA 60 Hz): 1.7
Max. Continuous Current (MCC in Amps): 2.9
Motor Resistance (Ohm) - Main: 16.8
Motor Resistance (Ohm) - Start: 16.8
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

**CCC Listed, CE Listed, GOST RUSSIA Listed, GOST
UKRAINE Listed**