



Model: AJK513T-GZ3C (CAJ9513T)

Product Description

Type: Reciprocating
Application: MBP/HBP - Medium/High Back Pressure
Refrigerant: R-22
Voltage/Frequency: 208-220V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V ~ 50HZ	10383	2616	3042	1188	8.73	2.2	2.56	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 22
Weight Unit of Measure: KG
Displacement (cc): 24.2
Oil Type: Synthetic Alkylate
Viscosity (cSt): 68
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 187-242
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 0
Rated Load Amps (RLA 50 Hz): 6.2
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 1.66
Motor Resistance (Ohm) - Start: 5.8
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed