



Model: AJK513Z-TZ1A (TAJ9513Z)

Product Description

Type: Reciprocating
Application: MBP/HBP - Medium/High Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	400V 3~ 50HZ	9966	2511	2920	1344	7.41	1.86	2.17	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)
EN12900	440V 3~ 60HZ	11671	2941	3419	1684	6.93	1.74	2.03	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 19
Weight Unit of Measure: KG
Displacement (cc): 24.2
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 475

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 17.3
Rated Load Amps (RLA 50 Hz): 2.8
Rated Load Amps (RLA 60 Hz): 2.8
Max. Continuous Current (MCC in Amps): 4.5
Motor Resistance (Ohm) - Main: 14.8
Motor Resistance (Ohm) - Start: 14.8
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

**CE Listed, GOST RUSSIA Listed, GOST UKRAINE
Listed, VDE Listed**