



Model: HGA2419ZCZ (HGA2426Z)

Product Description

Type: Rotary
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 230V ~ 60Hz 208V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 60HZ	1133	286	332	381	2.97	.75	.87	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)
EN12900	208V ~ 50HZ	884	223	259	310	2.85	.72	.84	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

General

Evaporating Temp. Range: -40°C to -10°C (-40°F to 14°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 11
Weight Unit of Measure: KG
Displacement (cc): 9.52
Oil Type: Polyvinylether
Viscosity (cSt): 68
Oil Charge (cc): 290

Electrical

Voltage Range (50 Hz): 187-230
Voltage Range (60 Hz): 207-253
Locked Rotor Amps (LRA): 12.9
Rated Load Amps (RLA 50 Hz): 2.3
Rated Load Amps (RLA 60 Hz): 2.3
Max. Continuous Current (MCC in Amps): 3.9
Motor Resistance (Ohm) - Main: 1.3
Motor Resistance (Ohm) - Start: 4.93
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, UL Recognized