



Model: HGA4467UFZ (HGA4467U)

Product Description

Type: Rotary
Application: HBP - High Back Pressure
Refrigerant: R-290
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 50HZ	4314	1087	1264	366	11.79	2.97	3.45	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 12
Weight Unit of Measure: KG
Displacement (cc): 9.52
Oil Type: Polyvinylether
Viscosity (cSt): 68
Oil Charge (cc): 290

Electrical

Voltage Range (50 Hz): 198-253
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 15
Rated Load Amps (RLA 50 Hz): 2
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 3
Motor Resistance (Ohm) - Main: 7.4
Motor Resistance (Ohm) - Start: 15
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, VDE Listed