

NLE10CN Energy-optimized LBP/MBP Compressor R290 115-127V 60Hz

General

Code number (pre-assembled CSIR start equipment)	105H6195
Approvals	UL984
Compressors on pallet	80

Application

Application	LBP/MBP			
Frequency	Hz	50	60	
Evaporating temperature	°F	–	-31 to 45	
Voltage range	V	–	95 - 135	
Max. condensing temperature continuous (short)	°F	–	149 (149)	
Max. winding temperature continuous (short)	°F	–	257 (275)	

Cooling requirements

Frequency	Hz	50			60		
Application		LBP	MBP	HBP	LBP	MBP	HBP
90°F		—	—	—	F ₂	F ₂	—
100°F		—	—	—	F ₂	F ₂	—
110°F		—	—	—	F ₂	F ₂	—
Remarks on application:							

Motor


Motor type	CSIR		
LRA (rated after 4 sec. UL984), HST LST	A	34.5	–
Cut in Current, HST LST	A	34.5	–
Resistance, main start winding (77°F)	Ω	1.6	4.4

Design


Displacement	cu.in	0.62
Oil quantity (type)	fl.oz.	10.2 (polyolester)
Maximum refrigerant charge	oz.	5.3
Free gas volume in compressor	fl.oz.	79.8
Weight without electrical equipment	lbs.	24.0

Dimensions

Height	inch	A	7.99
		B	7.76
		B1	—
		B2	—
Suction connector	location, I.D. in. angle	C	0.320-0.327 45°
	material comment	Copper Rubber plug	
Process connector	location, I.D. in. angle	D	0.252-0.259 25°
	material comment	Copper Rubber plug	
Discharge connector	location, I.D. in. angle	E	0.252-0.259 15°
	material comment	Copper Rubber plug	
Oil cooler connector	location, I.D. in. angle	F	—
	material comment	—	
Remarks:			



- S = Static cooling normally sufficient
- O = Oil cooling
- F₁ = Fan cooling 1.5 m/s (compressor compartment temperature equal to ambient temperature)
- F₂ = Fan cooling 3.0 m/s necessary
- SG = Suction gas cooling normally sufficient
- = not applicable in this area



ASHRAE LBP115V, 60Hz, fan cooling F₂

Evap. temp. in °F	-49	-40	-30	-20	-13	-10	0	10	14	20	30	32	40	41	45	50	59
Capacity in BTU/h			1216	1598	1919	2071	2638	3304	3599	4073	4950	5138	5938	6043	6475		
Power cons. in W			306	354	386	399	441	481	498	522	565	574	610	615	634		
Current cons. in A			4.62	4.91	5.10	5.18	5.43	5.69	5.79	5.95	6.24	6.30	6.56	6.60	6.74		
EER in BTU/Wh			3.97	4.51	4.97	5.19	5.99	6.87	7.23	7.80	8.76	8.96	9.73	9.83	10.2		

ASHRAE MBP/HBP115V, 60Hz, fan cooling F₂


Evap. temp. in °F	-49	-40	-30	-20	-13	-10	0	10	14	20	30	32	40	41	45	50	59
Capacity in BTU/h			1087	1428	1715	1850	2356	2948	3211	3631	4408	4575	5281	5374	5755		
Power cons. in W			303	351	382	395	436	476	492	517	558	567	603	607	626		
Current cons. in A			4.62	4.91	5.10	5.18	5.43	5.69	5.79	5.95	6.24	6.30	6.56	6.60	6.74		
EER in BTU/Wh			3.58	4.07	4.49	4.69	5.40	6.19	6.52	7.03	7.90	8.07	8.76	8.85	9.19		

EN 12900 LBP115V, 60Hz, fan cooling F₂

Evap. temp. in °F	-49	-40	-30	-20	-13	-10	0	10	14	20	30	32	40	41	45	50	59
Capacity in W			375	480	566	607	757	931	1008	1131	1357	1406	1610	1637	1748		
Power cons. in W			320	371	404	418	462	506	523	550	596	606	646	651	673		
Current cons. in A			4.62	4.91	5.10	5.18	5.43	5.69	5.79	5.95	6.24	6.30	6.56	6.60	6.74		
COP in W/W			1.17	1.29	1.4	1.45	1.64	1.84	1.93	2.06	2.28	2.32	2.49	2.51	2.6		

EN 12900 MBP115V, 60Hz, fan cooling F₂

Evap. temp. in °F	-49	-40	-30	-20	-13	-10	0	10	14	20	30	32	40	41	45	50	59
Capacity in W			340	441	524	563	708	877	952	1071	1290	1337	1536	1562	1669		
Power cons. in W			306	349	377	389	428	466	482	506	549	558	596	601	621		
Current cons. in A			4.54	4.78	4.94	5.00	5.2	5.40	5.48	5.60	5.82	5.87	6.06	6.09	6.20		
COP in W/W			1.11	1.26	1.39	1.45	1.66	1.88	1.97	2.12	2.35	2.40	2.58	2.60	2.69		



Accessories for	NLE10CN	Figure	Code number
Starting relay	1/4 in. spade connectors	a2	117U7018
Start. capacitor 280 µF	1/4 in. spade connectors	c	117U5025
Cover		b	103N2011
Cord relief		d	103N1010

Test conditions	EN 12900		ASHRAE	
	LBP	MBP	LBP	MBP
Condensing temperature	104°F	113°F	130°F	130°F
Ambient temperature	90°F	90°F	90°F	90°F
Suction gas temperature	68°F	68°F	90°F	95°F
Liquid temperature	no subcooling		90°F	115°F

Mounting accessories		Code number
Bolt joint for one comp.	Ø: 3/4 in.	118-1949
Bolt joint for one comp.	Ø: 5/8 in.	118-1946
Snap-on for one comp.	Ø: 5/8 in.	118-1947

Nidec GA Compressors accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Nidec GA Compressors reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Nidec Global Appliance Germany GmbH. All rights reserved. www.secop.com