



Model: RGA4492ZXA (RGA4492Z)

Product Description

Type: Rotary
Application: HBP - High Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 115V ~ 60Hz 100V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	100V ~ 50HZ	6572	1656	1925	739	8.89	2.24	2.6	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)
EN12900	115V ~ 60HZ	8256	2080	2419	913	9.04	2.27	2.64	5°C (41°F)	50°C (122°F)	32°C (90°F)	20°C (68°F)	50°C (122°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 13
Weight Unit of Measure: KG
Displacement (cc): 12.75
Oil Type: Polyvinylether
Viscosity (cSt): 68
Oil Charge (cc): 290

Electrical

Voltage Range (50 Hz): 90-110
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 115
Rated Load Amps (RLA 50 Hz): 9
Rated Load Amps (RLA 60 Hz): 9
Max. Continuous Current (MCC in Amps): 14
Motor Resistance (Ohm) - Main: .95
Motor Resistance (Ohm) - Start: 3.18
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, UL Recognized