



## Model: RGA5510EXA (RGA5510E)

### Product Description

**Type:** Rotary  
**Application:** HBP/AC - Air Conditioning  
**Refrigerant:** R-22  
**Voltage/Frequency:** 115V ~ 60Hz 100V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	10300	2596	3018	954	10.8	2.72	3.16	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
EN12900	115V ~ 60HZ	9205	2320	2697	897	10.26	2.59	3.01	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)
EN12900	100V ~ 50HZ	7440	1875	2180	732	10.16	2.56	2.98	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 27  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 14.208  
**Oil Type:** Synthetic Alkylate  
**Viscosity (cSt):** 53  
**Oil Charge (cc):** 250

#### Electrical

**Voltage Range (50 Hz):** 90-110  
**Voltage Range (60 Hz):** 103-127  
**Locked Rotor Amps (LRA):** 58.4  
**Rated Load Amps (RLA 50 Hz):** 9.8  
**Rated Load Amps (RLA 60 Hz):** 9.2  
**Max. Continuous Current (MCC in Amps):** 16  
**Motor Resistance (Ohm) - Main:** .58  
**Motor Resistance (Ohm) - Start:** 4  
**Motor Type:** PSC  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

cURus Recognized