



## Model: RKA5513CFZ (RK5513C)

---

### Product Description

**Type:** Rotary  
**Application:** HBP/AC - Air Conditioning  
**Refrigerant:** R-407C  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A

---

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 50HZ	9027	2275	2645	891	10.13	2.55	2.97	5°C (41°F)	50°C (122°F)	32°C (90°F)	15°C (59°F)	50°C (122°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 13  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 18.1  
**Oil Type:** Polyvinylether  
**Viscosity (cSt):** 68  
**Oil Charge (cc):** 430

#### Electrical

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 24  
**Rated Load Amps (RLA 50 Hz):** 4.5  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 7.5  
**Motor Resistance (Ohm) - Main:** 2.69  
**Motor Resistance (Ohm) - Start:** 5.15  
**Motor Type:** PSC  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed