



Model: THB1335YTS (THB1335YS)

Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-134a
Voltage/Frequency: 115V ~ 60Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	380	96	111	100	3.8	.96	1.11	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

General

Evaporating Temp. Range: -34.4°C to -12.2°C (-30°F to 10°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Static

Mechanical

Weight: 7
Weight Unit of Measure: KG
Displacement (cc): 3.79
Oil Type: Polyolester
Viscosity (cSt): 10
Oil Charge (cc): 243

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): 92-127
Locked Rotor Amps (LRA): 17.4
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 1.47
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 4.52
Motor Resistance (Ohm) - Start: 6.69
Motor Type: PTCS_IR
Overload Type: N/A
Relay Type: N/A

Agency Approval

cURus Recognized