



Model: THB4419YHZ

Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-134a
Voltage/Frequency: 208-220V ~ 60Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V ~ 60HZ	1830	461	536	277	6.61	1.66	1.94	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
CECOMAF	220V ~ 60HZ	1500	378	440	267	5.62	1.42	1.65	5°C (41°F)	55°C (131°F)	32°C (90°F)	32°C (90°F)	55°C (131°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Static

Mechanical

Weight: 8
Weight Unit of Measure: KG
Displacement (cc): 5
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 247.67

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): 187-242
Locked Rotor Amps (LRA): 10
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 1.69
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 9.22
Motor Resistance (Ohm) - Start: 24.54
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, cURus Recognized