



## Model: THB4422YCZ

### Product Description

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-134a  
**Voltage/Frequency:** 230V ~ 60Hz 208V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	230V ~ 60HZ	2190	552	642	340	6.44	1.62	1.89	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
CECOMAF	230V ~ 60HZ	1815	457	532	327	5.55	1.4	1.63	5°C (41°F)	55°C (131°F)	32°C (90°F)	32°C (90°F)	55°C (131°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 8  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 5.9  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 247.67

#### Electrical

**Voltage Range (50 Hz):** 187-230  
**Voltage Range (60 Hz):** 207-253  
**Locked Rotor Amps (LRA):** 11  
**Rated Load Amps (RLA 50 Hz):** 1.95  
**Rated Load Amps (RLA 60 Hz):** 1.9  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** 9.42  
**Motor Resistance (Ohm) - Start:** 17.38  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, cURus Recognized