



Model: THB4422YFZ

Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-134a
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A

Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	230V ~ 50HZ	1875	472	550	272	6.89	1.74	2.02	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
CECOMAF	230V ~ 50HZ	1560	393	457	270	5.78	1.46	1.69	5°C (41°F)	55°C (131°F)	32°C (90°F)	32°C (90°F)	55°C (131°F)

General

Evaporating Temp. Range: -15°C to 15°C (5°F to 59°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 8
Weight Unit of Measure: KG
Displacement (cc): 5.9
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 247.67

Electrical

Voltage Range (50 Hz): 198-253
Voltage Range (60 Hz): N/A
Locked Rotor Amps (LRA): 9
Rated Load Amps (RLA 50 Hz): 1.64
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 11.95
Motor Resistance (Ohm) - Start: 23.01
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, VDE Listed