



## Model: VSC9530XXG

Version: N/A

### Product Description

**Type:** Scroll  
**Application:** CBP - Commercial Back Pressure  
**Refrigerant:** MULTI  
**Voltage/Frequency:** 460V 3~ 60Hz 380-420V 3~ 50Hz

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
ARI (R-404A)	460V 3~ 60HZ	30324	7642	8879	4251	7.13	1.8	2.09	-6.7°C (20°F)	49°C (120°F)	35°C (95°F)	4.4°C (40°F)	49°C (120°F)

#### General

**Evaporating Temp. Range:** -23.3°C to 7.2°C (-10°F to 45°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 82  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 68.8  
**Oil Type:** Polyvinylether  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 1567

#### Electrical

**Voltage Range (50 Hz):** 342-462  
**Voltage Range (60 Hz):** 396-506  
**Locked Rotor Amps (LRA):** 60  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 8.3  
**Max. Continuous Current (MCC in Amps):** 13  
**Motor Resistance (Ohm) - Main:** 2.61  
**Motor Resistance (Ohm) - Start:** N/A  
**Motor Type:** 3PH  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, UL Recognized