Semi-Hermetic Condensing Units with BITZER Compressor Air-Cooled – Equipped with Oil and Suction Separator

Model: UC-2HES1-1HP

SKU: 141.551

Type: Uncased or Unshielded Cooling Type: Air-Cooled

## Included:

Oil and suction separator, crankcase heater, dual pressure switch KP17W (Danfoss). ERP helical air-cooled condenser, liquid receiver, safety valve, liquid filter, and sight glass.

For HFC refrigerants only.

## Important:

With R448A/R449A, at -31 °F, a head fan is required.

At -40 °F, additional cooling and suction gas superheat ≤36 °R are necessary.



## Características técnicas

Example image - your product may vary

Ambient Temperature	e (°F) 90	Compressor Mark/Mo	odel Bitzer 2HES-1Y
Number of Fans	2	Nominal Power	1 Hp
Airflow CFM	2	Power Supply	220 or 460V / 3Ph
Evaporation Tempera	ature °F -22	Compressor Type	Semi-Hermetic
Refrigerant	R134a / R448A / R449A	Power Consumption	760 W
Cooling Capacity* (W	1023	Max Amps (A)	3.8
COP (Coeff. of Perf.)	1,3	Suction Line	5/8"
Net Weight (Lbs)	150	Liquid Line	1/2"
Liquid Receiver (gal)	0.63	Dimensions LxWxH (	(in) 31.5" × 26" × 16.9"
Fan Power Supply	220/1		

<sup>\*</sup> Infórmenos sobre el refrigerante que se utilizará.





